


VIDA FREESTANDING BATH



Pictured - Vida freestanding 1675mm bath SKU - FSBTHVIDA1675



DESCRIPTION

The Vida freestanding bath can be purchased in 3 size variations.

The bath is also designed with a 15mm upstand around its perimeter to aid waterproofing between the bath and the wall linings. This makes it the most simple, and fastest bath to install for a shower over bath solution.

(see your merchant for bath screens and wall lining options)

The upstand is tightly pressed to make liner or tile installation easy, and watertight.

The Vida features solid mounted support feet which must be attached to the floor to support the base of the bath.

FEATURES

- Bath surface is 100% Solid acrylic
- 15mm pressed upstand around perimeter of Bath
- Generous bathing / showering area
- Fibreglass reinforced
- Bath stands on support rings

Dimension	Description	Bath Size		
		1525mm	1675mm	1800mm
А	Bath overall width	760mm	760mm	760mm
В	Bath overall height	590mm	590mm	590mm
С	Internal floor width	440mm	440mm	440mm
D	Internal depth	450mm	450mm	450mm
E	Bath length overall	1525mm	1675mm	1800mm
F	Internal floor length	1030mm	1180mm	1305mm
G	Upstand thickness +/- 2mm	7mm	7mm	7mm
Н	Upstand Height	15mm	15mm	15mm
I	Rim width	80mm	80mm	80mm
J	Waste width to external edge	380mm	380mm	380mm
К	Waste depth to external edge	290mm	290mm	290mm

ORDERING CODES

Description	SKU
1525mm x 760mm x 470mm Vida Freestanding Bath Only White	FSBTHVIDA1525
1675mm x 760mm x 470mm Vida Freestanding Bath Only White	FSBTHVIDA1675
1800mm x 760mm x 470mm Vida Freestanding Bath Only White	FSBTHVIDA1800

WARRANTY INFORMATION

All bathroomware products supplied by Fibre Systems carry our Quality Assurance and Product Warranty. We use the highest quality materials available and manufacture these in accordance with New Zealand specifications and requirements to ensure that all products are fit for the intended purpose for which they are designed. Our customers peace of mind is of paramount importance to us.

Warranty Periods

Showers 10 years Drop In baths 10 years Shower Screens and Doors 10 years Black Coating on Framework 5 years Freestanding Baths 5 years Accessories 2 years



Warrantu Exclusions

The product must be installed according to the instructions supplied.

The water supply temperature applied to the product must not exceed 55 degrees Celsius.

Commercial applications (where products are installed in a building where occupancy is via a commercial arrangement i.e. rental property, hotel, hostel etc.) are restricted to a 2 year warranty on all products.

CLEANING AND MAINTENANCE

Bathroom products are used often and the following is our suggestion on how to clean and care for them.

Shower Wall

We use Durosan premium quality sanitaryware grade Acrylic. It is, by design, very robust and chemical resistant. A soft damp cloth with non-abrasive cleaners should be used. Use only non-abrasive cleaners that are recommended for acrylic products.

We manufacture our Shower Trays and Baths using a Solid Acrylic Surface. Most other shower trays are manufactured using a veneer acrylic surface. The great advantage is that small scratches can be removed easily by using fine cutting compound. Again, the same basic cleaning methods as the wall are recommended.

Shower Doors and Glass

All glass is compliant to AS/NZS 2208. We suggest that the glass surfaces are wiped down or squeegeed following use to remove excess water. For best results use a trusted glass cleaner.

Metal Framework

Should be cleaned using a soft damp cloth with non-abrasive cleaner. Note that on round showers, the bottom rollers are easy release for ease of cleaning. If chemical spray cleaners are used, avoid direct contact with the rollers and guides and ensure the shower is rinsed off to avoid residue build up.

Weather Seals and Drip Strips

Can be removed if required for cleaning, and can be replaced when they no longer look their best. Refer to the spare parts and accessories section of our website for more details.

Note - If the Glass has been treated follow specific cleaning instructions from the system provider.

