

Class 1

Symphony Framed Shower Door Sets

Product Disclosure Information Self-Assessment

Version: Symphony Framed Shower Door Sets V1

Product name	Symphony Framed Shower Door Sets
Product line	Symphony Framed Shower Door Sets
Product identifier	Symphony Framed Shower Door Sets are sold as component of Symphony Shower Cubicles, and as individual items as SKU Prefix D, DA, DG, DR, DCS,

Product description

- Symphony Framed shower door sets are manufactured from 6mm toughened safety glass which conforms to AS/NZS2208 standard.
- Symphony Framed shower door sets are available in pivot and sliding door configurations.
- Symphony Framed shower door sets are available in Round corner, Square corner, Alcove, and Angle Corner configurations.
- Symphony Framed shower door sets include components made from high quality corrosion resistant alloy.
- Symphony Framed shower doors and components are designed to be easily cleaned, with silicone application required only in external areas of the shower.

Relevant building code clauses

Contributions to compliance

- B2.3.1(c) and B2.3.2: Symphony Framed Shower Door sets have a durability of at least 5 years when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.2(c) Symphony Framed Shower Door sets have been designed to inhibit Internal moisture to building elements when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.3.5, E3.3.6 Symphony Framed door sets are constructed from water impervious material which can be easily cleaned and maintained, and are constructed to prevent water splash penetrating wall linings or concealed spaces.
- F2.3.1 Symphony Framed door sets are safe when handled and used in everyday showering.
- F2.3.3 Symphony Framed Shower Door sets are manufactured from 6mm Toughened safety glass which conforms to AS/NZS2208 standard

First party self-assessment generated Oct 10, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=4a38ddd73f8f1e730dff8d374aa0365d2b8c8bb>

Get BPIR Ready | bpir.nz

Scope of use

- Symphony Framed Shower Door Sets intended for use in domestic bathrooms
- Symphony Framed Shower Shower Door sets are manufactured from AS/NZS2208 compliant toughened safety glass
- Symphony Framed Shower Shower Door sets are not intended for use in accessible facilities

Conditions of use

- Symphony Framed Shower Door Sets must be installed in accordance with applicable installation instructions
- The maximum water temperature is 55° Celcius
- This product is easy to clean and impervious to water
- Are compatible with Symphony Shower Trays and wall linings
- Are not intended for use in accessible facilities

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Symphony Round Corner Shower Door Installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/
Symphony Square 2 sided Pivot Shower door installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/
Symphony 2 Sided Sliding door Installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/
Symphony Alcove Sliding door Installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/
Symphony Alcove Pivot door Installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/
Symphony Angle corner pivot door Installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/
V Slider Square corner sliding door Installation Instructions (Installation)		https://symphonyshowers.co.nz/installation-instructions/

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Please Contact Fibre Systems Ltd

First party self-assessment generated Oct 10, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=4a38ddd73f8f1e730dff8d374aa0365d2b8c8bb>

Get BPIR Ready | bpir.nz

Legal and trading name of importer	Fibre Systems Limited
Importer address for service	77 Cryers Road Auckland 2013
Importer website	www.symphonyshowers.co.nz
Importer NZBN	9429038358470
Importer email	sales@fibresystems.co.nz
Importer phone number	09 274 7423

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Other (custom)

Building code performance clauses

All relevant building code performance clauses listed in this document:

Class 1

Symphony Acrylic 2 Sided Round Corner Shower Trays

Product Disclosure Information Self-Assessment

Version: Symphony 2 Sided Round Corner Shower Trays

Product name	Symphony Acrylic 2 Sided Round Corner Shower Trays
Product line	Symphony Acrylic 2 Sided Round Corner Shower Trays are sold individually and as a component of Symphony Shower Cubicles
Product identifier	Component of all 2 sided Round Symphony Shower Cubicles, and sold individually under SKU prefix TFR

Product description

- Symphony 2 Sided Round Corner Acrylic Shower Trays are a component of a complete Symphony Shower Cubicle, and sold individually under SKU code Prefix TFS.
- Symphony 2 Sided Round Corner Acrylic Shower trays are manufactured from Sanitary grade solid Acrylic which is laminated and reinforced with Fibreglass. The Acrylic surface is easy to clean and features a Gloss Neutral white finish.
- For durability these trays feature integrated support feet, and are designed to be installed onto Solid flooring substrates such as Timber or Concrete.
- They also feature a 40mm high Upstand where wall linings meet the shower tray to prevent water leakage, and corner drains for water control.

Relevant building code clauses

Contributions to compliance

- B2.3.1(c) and B2.3.2: Symphony Shower Trays have a durability of at least 5 years when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.2(c) Symphony Shower Trays have been designed to inhibit Internal moisture to building elements when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.3.3, E3.3.4, E3.3.5, E.3.3.6 Symphony Shower Trays are made from non - porous Sanitary Grade Acrylic which provides an impervious and easily cleaned surface.
- F2.3.1: Symphony Shower trays are safe when handled, and used in everyday showering.

Scope of use

First party self-assessment generated Sep 27, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=00ac2204d55b9c806cc46950d136a3ee352878e2>

Get BPIR Ready | bpir.nz

- Symphony Shower Trays are designed for Domestic bathrooms.
- They are suitable for cold and hot water use (maximum temperature 55° C)
- Symphony Shower Trays are compatible with 90mm Shower Waste Outlets

Conditions of use

- Symphony Shower Trays must be installed in accordance with installation manual "Tray and Wall Liner".
- The maximum water temperature is 55° Celcius
- This product is easy to clean and impervious to water
- Is compatible with 90mm Easy clean waste outlets which comply with AS/NZS3500 and AS2887. -
- Symphony Shower Trays are not intended for use in accessible facilities.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Symphony Shower Tray and Wall installation Manual (Installation)	v1	https://symphonyshowers.co.nz/installation-instructions/

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Please Contact Fibre Systems Ltd
Legal and trading name of importer	Fibre Systems Limited
Importer address for service	77 Cryers Road Auckland 2013
Importer website	www.fibresystems.co.nz
Importer NZBN	9429038358470
Importer email	sales@fibresystems.co.nz
Importer phone number	09 274 7423

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

First party self-assessment generated Sep 27, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=00ac2204d55b9c806cc46950d136a3ee352878e2>

Get BPIR Ready | bpir.nz

Appendix

BPIR Ready selections

Category: Other (custom)

Building code performance clauses

All relevant building code performance clauses listed in this document:

First party self-assessment generated Sep 27, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=00ac2204d55b9c806cc46950d136a3ee352878e2>

Get BPIR Ready | bpir.nz

Class 1

Symphony Acrylic Shower Wall Liners

Product Disclosure Information Self-Assessment

Version: Symphony Acrylic Shower Wall Liners v1

Product name	Symphony Acrylic Shower Wall Liners
Product line	Symphony Acrylic Shower Wall Liners
Product identifier	Component of all Symphony Shower cubicles listed in Range and sold individually under SKU prefix LB

Product description

- Symphony Shower Wall Liners are a component of a complete Symphony Shower Cubicle.
- Symphony Shower Wall Liners are available in Flat and Moulded Wall configurations.
- Symphony Shower Wall Liners are made from High Quality Acrylic with an ABS lining.
- Symphony Wall Liners meet European Standard En-13559-2003.
- Symphony Wall Liners feature the highest level of Colour Fastness, UV Resistance, Resistance to Hot Water, Chemical and Stain Resistance and Stress Cracking.
- The Acrylic surface is easy to clean and features a Gloss Neutral white finish,

Relevant building code clauses

Contributions to compliance

- B2.3.1(c) and B2.3.2: Symphony Acrylic Wall Linings have a durability of at least 5 years when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.2(c) Symphony Acrylic Wall Linings have been designed to inhibit Internal moisture to building elements when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.3.3, E3.3.4, E3.3.5, E.3.3.6 Symphony Acrylic Wall Linings are made from non - porous Acrylic which provides an impervious and easily cleaned surface.
- F2.3.1: Symphony Acrylic Wall Linings are safe when handled, and used in everyday showering.

Scope of use

- Symphony Acrylic Wall Linings are designed for Domestic bathrooms.
- They are suitable for cold and hot water use (maximum temperature 55° C)
- Are compatible with Symphony Acrylic Shower trays and doors

Conditions of use

- Symphony Shower Wall Liners must be installed in accordance with installation manual "Tray and Wall Liner".
- The maximum water temperature is 55° Celcius
- This product is easy to clean and impervious to water Is compatible with Symphony Shower Trays and Doors
- Symphony Shower Wall Linings are not intended for use in accessible facilities

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Symphony Shower Tray and Wall installation Manual (Installation)	V1	https://symphonyshowers.co.nz/installation-instructions/

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Contact Fibre Syetems Ltd
Legal and trading name of importer	Fibre Systems Limited
Importer address for service	77 Cryers Road Auckland 2013
Importer website	www.fibresystems.co.nz
Importer NZBN	9429038358470
Importer email	sales@fibresystems.co.nz
Importer phone number	09 274 7423

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

First party self-assessment generated Oct 2, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=a29511b3fc15285c9fa8c5f0ad08d4be76d00b08>

Get BPIR Ready | bpir.nz

BPIR Ready selections

Category: Other (custom)

Building code performance clauses

All relevant building code performance clauses listed in this document:

First party self-assessment generated Oct 2, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=a29511b3fc15285c9fa8c5f0ad08d4be76d00b08>

Get BPIR Ready | bpir.nz