

Class 1

Symphony Pinnacle Shower Wall Linings

Product Disclosure Information Self-Assessment

Version: Symphony Pinnacle Wall Linings V1

Product name	Symphony Pinnacle Shower Wall Linings
Product line	Symphony Pinnacle Shower Wall Linings
Product identifier	Sold as sheets or as an Upgrade Kit to applicable Symphony Acrylic Shower Cubicles. Individual Sheets are available in the following patterns and colours - Subway Gloss White Tile, Hexagonal Gloss White Tile, Slate Textured Grey, White, Black, Vertical Textured Tile Pattern in Grey, White, Black and Gloss Marble Effect

Product description

- Pinnacle Wall Lining Sheets are either sold as individual sheets, or as an upgrade kit to applicable Syphony Showers Cubicles.
- Pinnacle Wall Lining Sheets vary in thickness dependent on pattern and finish design. Thickness ranges from 3.5mm to 4.5mm
- Pinnacle Wall Lining Sheets are manufactured from Resin/ Fibreglass composite material which is molded in high temperature, high pressure single molded sheets.
- Pinnacle Wall Lining Sheets have a solid surface, and are finished in either Gloss, or Slate Effect and are easily cleaned.
- Pinnacle Wall linings which feature tiled patterns have easy to clean "grout" lines and precise radius corners on tiles to make cleaning easy and inhibit dirt built up.
- Pinnacle Wall lining components, are manufactured from High Grade Aluminum and are finished to match the wall lining colour.

Relevant building code clauses

Contributions to compliance

- B2.3.1(c) and B2.3.2: Symphony Pinnacle Wall Linings and components have a durability of at least 5 years when installed in accordance with installation instructions. Refer to the installation requirements for further information.
- E3.2(c) Symphony Pinnacle Wall Linings and components have been designed to inhibit Internal moisture to building elements when installed in accordance with installation instructions. Refer to the installation requirements for further information.

First party self-assessment generated Oct 4, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=100f8111c91659756318d8dd2b23d021a3227ebb>

Get BPIR Ready | bpir.nz

- E3.3.3, E3.3.4, E3.3.5, E.3.3.6 Symphony Pinnacle Wall Linings and components are made from non - porous material which provides an impervious and easily cleaned surface.
- F2.3.1: Symphony Pinnacle Wall Wall Linings and components are safe when handled, and used in everyday showering.

Scope of use

- Symphony Pinnacle Wall Linings are designed for Domestic bathrooms.
- They are suitable for cold and hot water use (maximum temperature 55° C)
- Are compatible with Symphony Acrylic, and Symphony Pinnacle Shower trays and doors. They also can be installed as a wall lining sheet in any showering area.

Conditions of use

- Symphony Pinnacle Wall Liners must be installed in accordance with installation manual.
- The maximum water temperature is 55° Celcius
- This product is easy to clean and impervious to water
- Is compatible with Symphony Acrylic Shower Trays and Doors, and Symphony Pinnacle Trays.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Pinnacle Wall Lining Installation Instructions (Installation)	V1	https://symphonyshowers.co.nz/installation-instructions/

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Please Contact Fibre Systems Ltd
Legal and trading name of importer	Fibre Systems Limited
Importer address for service	77 Cryers Road Auckland 2013
Importer website	www.symphonyshowers.co.nz
Importer NZBN	9429038358470
Importer email	sales@fibresystems.co.nz
Importer phone number	09 274 7423

First party self-assessment generated Oct 4, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=100f8111c91659756318d8dd2b23d021a3227ebb>

Get BPIR Ready | bpir.nz

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Other (custom)

Building code performance clauses

All relevant building code performance clauses listed in this document: